

Technical specifications

	Citoborma 190	Citoborma 290	Citoborma 290 B	Citoborma 290 AB
Number of drill heads	1	2	2	2
Max. pile height (mm)	60	60	60	60
Max. paper width (mm)	470	470	470	470
Max. throat depth (mm)	105	105	105	105
Drill bit sizes (mm)	2 – 14 (2 – 20)	2 – 10 (2 – 14)	2 – 10 (2 – 14)	2 – 14
Distance between centres (mm)	–	80	45 – 160	45 – 160
Time / stroke (s)	Operator speed	Operator speed	Operator speed	3,3
Power stroke	–	–	–	✓
Foot treadle stand	•	•	•	–
Power supply	230 V, 50 Hz (400 V, 50 Hz)	230 V, 50 Hz (400 V, 50 Hz)	230 V, 50 Hz (400 V, 50 Hz)	400 V, 50 Hz
Power consumption (kW)	0,5	0,5	0,5	0,9
H x W x D net (cm)	70 x 64 x 60	70 x 64 x 60	73 x 64 x 60	158 x 64 x 60
Weight, net (kg)	55	59	69	165
H x W x D (cm) gross	80 x 80 x 80	80 x 80 x 80	80 x 80 x 80	165 x 80 x 80
Weight, gross (kg)	75	80	90	195
✓ Standard • optional – not available				